



02/09/99

ATTORNEYS AT LAW

767 THIRD AVENUE, NEW YORK, N.Y. 10017-2023

STEPHEN H. FRISHAUF
LEONARD HOLTZ
HERBERT GOODMAN
WILLIAM R. WOODWARD (1914-1994)
THOMAS LANGER
MARSHALL J. CHICK
RICHARD S. BARTH
DOUGLAS HOLTZ
ROBERT P. MICHAL
TELEPHONE: (212) 319-4900
FACSIMILE: (212) 319-5101

Asst. Commissioner for Patents
Washington, D.C. 20231

Date of Deposit: February 9, 1999

I hereby certify that this paper is being deposited with the United States Postal Service "Express Mail Post Office to Addressee" service under 37 CFR 1.10 on the date indicated above and is addressed to the Asst. Commissioner for Patents, Washington, D.C. 20231

Barbara Villani

Attorney Docket No. 990095/LH

542 U.S. PTO
09/246913
02/09/99

Transmitted herewith for filing UNDER SMALL ENTITY STATUS is the patent application of

Inventor(s): Kunihiko TANAKA

Title: "FOOD AND DRINK CONVEYING SYSTEM"

Priority Claim (35 U.S.C. 119) is made, based upon:

Japan	No. 10-31538	February 13, 1998
Japan	No. 10-350201	December 9, 1998

Enclosed herewith are:

- ☒ Specification (Description, Claims, Abstract): Pages 1 - 19 ; Number of claims 1 - 7
- ☒ Declaration and Power of Attorney ☒ executed; ☐ unexecuted (supplied for information purposes)
- ☒ 11 Sheets of drawings, Figures 1 - 13 ☒ Formal ☐ Informal
- ☒ Assignment and "Patents" Recordation Form Cover Sheet (PTO-1595) & \$40. RECORDATION FEE.
- ☒ Certified copy (ies) of priority document(s) identified above
- ☐ Information Disclosure Statement; ☐ Form PTO-1449
- ☐ Preliminary Amendment
- ☒ Verified Statement(s) Claiming Small Entity Status
- ☒ Receipt Postcard

	Number Filed		Number Extra	Rate	Calculations
Total Claims	<u>7</u> - 20	=	<u>0</u>	x \$ 9.00	= \$ _____
Independent Claims	<u>1</u> - 3	=	<u>0</u>	x \$39.00	= \$ _____
MULTIPLE DEPENDENT CLAIMS				+\$130.00	= \$ _____
				BASIC FEE	\$ 380.00
Total of above Calculations					\$ <u>380.00</u>

To the extent not tendered by check, authorization is given to charge any fees under 37 CFR 1.16 and 1.17 during pendency of the application, or to credit any overpayment, to Deposit Account No. 06-1378. Duplicate copy of this letter is enclosed.

FRISHAUF, HOLTZ, GOODMAN, LANGER & CHICK, P.C.

By: Thomas Langer
Thomas Langer, Reg. No. 27,264
for Leonard Holtz, Reg. No. 22,974

11/10/98

LH:bv

DECLARATION SUPPORTING CLAIM FOR SMALL ENTITY STATUS

The undersigned hereby declare(s) that this statement is made to support a claim by the below identified entity for purposes of paying reduced fees under Secs. 41(a) and (b) of Title 35, United States Codes, with regard to an invention entitled FOOD AND DRINK CONVEYING SYSTEM

invented by _____ and described in
☒ the specification filed herewith.
☐ application Serial No. _____, filed _____
☐ Patent No. _____, issued _____

☐ a. I am/we are the inventor(s) of the above-identified invention.
☐ b. I/we would qualify as (an) independent inventor(s) as defined in 37 CFR 1.9(c) if I/we had made the above-identified invention, and rights under contract law with regard to the above-identified invention have been conveyed to and remain with me/us.

☐ the owner
☒ c. I am ☐ an official of the below-identified small business concern; rights under contract law with regard to the above-identified invention have been conveyed to and remain with the below-identified small business concern; and this concern qualifies as a small business concern as defined in 13 CFR 121. 3-18, and reproduced in 37 CFR 1.9(d), for purposes of paying reduced fees under sections 41(a) and (b) of Title 35, United States Code, in that the number of employees of the concern, including those of its affiliates, does not exceed 500 persons, said number being determined and said affiliates being defined in 13 CFR 121. 3-18.

No rights in the invention have been assigned, granted, conveyed or licensed or further assigned, granted, conveyed or licensed, and there is no obligation under contract or law to assign, grant, convey or license, or further assign, grant, convey or license such rights to any person who could not be classified as an independent inventor under 37 CFR 1.9(c) if that person had made the invention, or to any concern which would not qualify as a small business concern under 37 CFR 1.9(d) or a nonprofit organization under 37 CFR 1.9(e).

Each person, concern or organization to which any rights in the invention have been assigned, granted, conveyed, or licensed or further assigned, granted, conveyed, or licensed or further assign, grant, convey or license, or as to where there is an obligation under contract or law to assign, grant, convey, or license such rights is listed below:

- ☐ no such person, concern, or organization
☐ persons, concerns or organizations listed below *
 *NOTE: Separate verified statements are required from each named person, concern or organization having rights to the invention averring to their status as small entities. (37 CFR 1.27)

FULL NAME _____
 ADDRESS _____
☐ INDIVIDUAL ☐ SMALL BUSINESS CONCERN ☐ NONPROFIT ORGANIZATION

FULL NAME _____
 ADDRESS _____
☐ INDIVIDUAL ☐ SMALL BUSINESS CONCERN ☐ NONPROFIT ORGANIZATION

I/we acknowledge the duty to file, in this application or patent, notification of any change in status resulting in loss of entitlement to small entity status prior to paying, or at the time of paying, the earliest of the issue fee or any maintenance fee due after the date on which status as a small entity is no longer appropriate. (37 CFR 1.28(b))

I/we hereby declare that all statements made herein of my/our own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code, and that such willful false statements may jeopardize the validity of the application, any patent issuing thereon, or any patent to which this declaration is directed.

Kunihiko TANAKA *Kunihiko, Tanaka* February 5, 1999
 NAME SIGNATURE DATE

KURA CORPORATION LTD. 1035-2, Fukasaka, Sakai-shi, Osaka JAPAN
 NAME OF SMALL BUSINESS CONCERN ADDRESS

NAME SIGNATURE DATE

TITLE _____

000000-270720

FOOD AND DRINK CONVEYING SYSTEM

BACKGROUND OF THE INVENTION

Field of the Invention

5 The present invention relates to a food and drink conveying system which in an eating house, particularly in a sushi bar, makes a circulation of e.g. dished-up sushi by means of a conveying path so that customers can take the circulating foods and drinks at their own choice.

Description of the Prior Art

10 There are eating houses, such as sushi bars, adopting a food and drink conveying system having a conveying path which circulates along lots of tables or a counter set in the eating house or sushi bar. Foods (e.g. sushi) and drinks dished up on plates are served to the conveying path as occasion calls so that customers at the tables can take and eat a variety of foods and
15 drinks passing in order through the conveying path at their own choice.

Incidentally, in this food and drink conveying system, the foods and drinks dished up on the plates are usually served to the conveying path as occasion calls, irrespective of the customers' liking, but sometimes are served to meet the customers' orders.

20 When ordering, the customer must watch the conveyance of his/her order and sometimes overlooks his/her order passing past him/her, in the case of which the orderer must wait until his/her order is re-circulated through the conveying path before him/her and, what is worse, another person sometimes may take his/her order away without knowing it before
25 reaching him/her.

SUMMARY OF THE INVENTION

In consideration of this circumstance, the present invention has been developed. It is the object of the invention to provide a food and drink conveying system which enables a food or drink ordered, served to and
5 conveyed through a conveying path to surely be received by the orderer, without any fear of the ordered food or drink being taken out on the way to the orderer's place by another person by mistake.

To achieve the object above, the present invention provides a food and drink conveying system comprising a conveying path for making a
10 circulation of a plurality of containers each containing therein food or drink; a plurality of tables arranged along the conveying path; a conveying container which contains therein the container placing thereon the as-ordered food or drink and is placed on the conveying path; and noticing means for giving an orderer a notice of an arrival of his/her order contained
15 in the conveying container at a place near the orderer's table.

The noticing means may be formed by a speaker provided either in the conveying container or at the table side, so that the arrival of the order can be announced by means of it.

Additionally or alternatively, the noticing means may be formed by a
20 lamp provided in the conveying container to give the orderer a notice of the arrival of his/her order by lightening or flashing the lamp on and off when the order comes near the orderer's table.

The conveying container is provided with an input portion to which a designated table's mark is input and operation control means for controlling
25 operation of the noticing means by an input by means of the input portion.

The conveying container may have a retracting portion in which the container is kept retracted until a notice by means of the noticing means is started and from which the container is exposed to be taken out when the notice by means of the noticing means is started.

5 Further, it is preferable that the operation control means is provided with a timer facility in which traveling time for the conveying container to travel to the individual tables is preset and the conveying path is provided with a timer start gate portion for letting the timer of the timer facility start so that at a point in time when a conveying container placed on the
10 conveying path passes the timer start gate portion, the timer of the timer facility can be started.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a schematic plan view of an interior of an eating house in which a food and drink conveying system of the invention is set;

15 FIG. 2 is a sectional view of a conveying container placed on a conveying path of the food and drink conveying system, with a plate retracted in a retracting portion of the conveying container;

FIG. 3 is a side view of the conveying container of FIG. 2;

FIG. 4 is a sectional view of the conveying container of FIG. 2, with the
20 plate exposed from the retracting portion;

FIG. 5 is a side view of a part of the food and drink conveying system showing the state of conveying containers and plates being placed on the conveying path and conveying;

FIG. 6 is a schematic illustration showing another embodiment of the
25 conveying container;

FIG. 7 is a schematic plan view of the interior of the eating house in which a modified food and drink conveying system of the invention is set;

FIG. 8 is a schematic side view of a modified conveying container;

FIG. 9 is a structural drawing of the modified food and drink
5 conveying system;

FIG. 10 is a schematic plan view of the interior of the eating housing in which a further modified food and drink conveying system of the invention is set;

FIG. 11 is an enlarged plan view of a principal part of the food and
10 drink conveying system of FIG. 10;

FIG. 12 is an enlarged sectional view of the same; and

FIG. 13 is a structural drawing of the embodiment of the food and drink conveying system shown in FIG. 10.

DETAILED DESCRIPTION OF THE EMBODIMENTS

15 Referring now to the accompanying drawings, examples of the preferred embodiments of the present invention directed to a food and drink conveying system will be described below. It is to be understood, however, that the scope of the invention is by no means limited to the illustrated embodiments.

20 FIG. 1 shows an interior of a sushi bar as viewed from top in which there are provided a plurality of tables 2a and a counter 2b set in a dinning area 1; a compartment housing 4 arranged along a front side of a kitchen 3 and the tables and counter 2a, 2b; and a food and drink conveying system 6 having a conveying path 7, circularly arranged on the compartment housing
25 4, for circularly conveying foods, such as sushi R, and drinks dished up on

plates 5 in the kitchen 3.

The compartment housing 4 having a box shape in section is formed by spaced apart, opposite, side walls 41, a top wall 42, and a bottom wall (not shown) connecting between the both side walls 41 at upper and lower ends thereof.

The compartment housing 4 comprises a first housing portion 4a, arranged along the front side of the kitchen 3, for separating the kitchen 3 from the dinning area 1; second and third housing portions 4b, 4c bending from both lengthwise ends of the first housing portion 4a and extending in parallel into the dinning area 1. The tables 2a and the counter 2b are arranged alongside the side walls 41 at the second and third housing portions 4b, 4c, and chairs 21 are arranged at the tables and the counter 2a, 2b.

The tables 2a and the counter 2b are marked with (A), (B), (C), (D), (E), (F), (G), (H), (I) and (J), as shown in FIG. 1. The counter 2b is marked in association with the individual chairs 21, as illustrated. Hereinafter, the table and counter 2a, 2b sometimes are simply referred to as the table.

The conveying path 7 comprises a recess 71 provided in the top wall 42 of the housing portions 4a, 4b and 4c; and a flat endless chain 73 which moves in circulation in the recess 71 by motor drive while it is guided along guide walls 72 provided at both widthwise sides of the recess 71, as shown in FIGS. 2, 3 and 5. As shown in FIG. 5, the plates 5 each putting thereon food or drink are placed directly on the flat chain 73 of the conveying path 7 to convey the plates 5 in circulation.

EMBODIMENT 1

The food and drink conveying system 6 above comprises a conveying container 8 to put thereon an ordered food or drink and be placed on the conveying path 7, and noticing means 84, 85 for giving an orderer a notice of an arrival of his/her order placed on the conveying container 8 at a place near the orderer's table.

Specifically, the conveying container 8 includes, as shown in FIGS. 2 to 4, a box-like casing 81 opening at the top and having at a side surface thereof an input portion 82 having press button switches 83 which are marked corresponding to the tables marked with (A), (B), (C), (D), (E), (F), (G), (H), (I) and (J) so that the press button switch 83 having the mark corresponding to the orderer's table can be pressed to input the designated table's mark to the input portion.

The casing 81 is provided with a speaker 84 and a lamp 85 forming the noticing means so that when the order comes near the orderer's table, the arrival of the order can be noticed to the orderer by means of announcement from the speaker 84 and the lightening or flashing of the lamp 85.

The flat chain 73 moves in circulation with a uniform speed and thus the dished-up plates put on the conveying path 7 in the kitchen 3 travel between the kitchen 3 and the respective tables 2 in individual substantially fixed time. In view of this, a timer 93 is used as an operation control means for controlling the operation of the noticing means 84.

Individual time of the timer is preset for each of the tables so that at a point in time when any one of the press button switches 83 of the input portion 82 is pressed, the timer 93 can be put in motion (started) in accordance with the individual preset time.

After the expiration of a preset time interval after the timer 93 is put in motion by the input of the input portion 82, the announcement from the speaker 84 and the lightening of the lamp 85 are started.

Further, the casing 81 is provided in its interior with a retracting portion 86 in which the plate 5 is kept retracted until the notice by means of the speaker 84 and the lamp 85 is started and from which the plate 5 is exposed to be taken out when the notice by means of the speaker 84 and the lamp 85 is started.

The retracting portion 86 is provided with a lift 88 having a table member 87 for placing thereon the plate 5. When the plate 5 is placed on the lift 88 in the kitchen 3, the lift is in its highest level, as shown in FIG. 4. When a reset button switch 89 provided in the casing 81 is pressed to trigger the reset, the plate 5 is completely retracted into the retracting portion 86, as shown in FIG. 2. Then, the timer is put in motion by the input of the input portion 82. At the point in time when the notice by means of the speaker 84 and lamp 85 of the noticing means is started, the lift 88 is raised up to the highest level to project the plate 5 from the retracting portion 86.

The elevating motion of the lift 88 is effected by driving a motor 90 provided at a side of the casing 81 to rotate a driving shaft 92 of the lift 88 via a bevel gear 91 driven in association with the motor 90. The lift 88 is raised by the drive of the motor so that the plate 5 can be exposed just as the notice by means of the speaker 84 and the lamp 89 is started. The lift 88 is lowered by reversing the motor 90 at the push of the reset button switch 89.

With this constructed food and drink conveying system, when a food is ordered from a customer, the ordered food is dished up on the plate 5 in the

kitchen 3, and then the plate 5 is placed on the table member 87 of the conveying container 8 and is retracted in the retracting portion 86 at the push of the reset button switch 89.

Then, the press button switch 83 having the mark corresponding to the orderer's table is pressed to input the designated table's mark to the input portion. Then, the conveying container 8 is placed on the flat chain 73 of the conveying path 7, as shown in FIG. 5, to convey it to the dining area 1, together with other dished-up plates 5 placed directly on the flat chain 73.

In the conveying container 8 placed on the conveying path 7, the preset timer 93 is put in motion at the push of the press button switch 83 and runs out near the orderer's table. Then, the speaker 84 and the lamp 85 are put in motion for announcement and lightening, respectively, and the lift 88 is synchronously raised by the drive of the motor 90 to project the plate 5 from the retracting portion 86. Thus, the orderer can surely aware of his/her order arriving at his/her table even in the middle of eating and drinking and chatting.

Besides, since the order is kept retracted in the retracting portion 86 of the conveying container 8 until it comes near the orderer's table, it can be avoided being taken out at some mid point in the conveying path 7 by another customer.

The noticing means which in illustration above is formed by both the speaker 84 and the lamp 85 for providing the audible and visual notices may be formed by either of them.

Also, the table member 87 may be configured in the form of a doll, for

example, so that the order can be presented by using such a doll-like table member.

EMBODIMENT 2

The configuration of the conveying container may be modified such
5 that the plate 5 can be covered with, for example, a spherical open/close cover, as shown in FIG. 6.

Specifically, the conveying container 80 shown in FIG. 6 is provided with a pair of vertically divided, semi-spherical cover members 181 which are arranged with their openings confronting each other and a geared
10 interlocking mechanism 184 which is composed of a pair of gears 182, 183 provided at the bottom of the cover members 181, so that when the timer 93 runs off, the both cover members 181 are opened by the drive of a motor (not shown) associated with one of the gears 182 of the geared interlocking mechanism 184.

15 With this configured conveying container, since the food or drink on the plate 5 is kept covered with the cover members 181 until it reaches the orderer's table, the order can be conveyed safely as well as be avoided being taken out at some midpoint in the conveying path 7 by another customer.

EMBODIMENT 3

20 FIGS. 7 to 9 show a modified embodiment of the present invention. As the basic construction of the food and drink conveying system 6 of this embodiment is identical to that of the embodiment 1, the difference in construction only will be described below.

In the embodiment shown in FIGS. 7 to 9, a microcomputer 94 is used
25 as the operation control means, and a timer facility 95 in which individual

traveling time for a conveying container 800 to travel to the respective tables is preset is constructed on a program of the microcomputer 94. Also, a sensor 96 for detecting infrared radiation of timer start gate portions 100a, 100b discussed later is connected to an input portion of the microcomputer 94. At a point in time when the sensor 96 detects infrared radiation of the timer start gate portions 100a, 100b, the timer preset corresponding to the traveling time for the conveying container to travel to the table having the mark input to the input portion 820 is started.

The timer start gate portions 100a, 100b for starting the timer of the timer facility 95 are provided at the conveying path 7. In the illustrated embodiment, the first and second timer start gate portions 100a, 100b are set at entrance sides of the conveying path 7 in the second and third housing portions 4b and 4c so that they can apply infrared rays in such a manner as to intersect the conveying path 7.

In the timer facility 95 is preset the individual traveling time required for the conveying container 800 to travel to the individual tables. For the tables marked with (A), (B), (C) and (D), the individual traveling time is preset for the conveying container 800 to travel between the first timer start gate 100a and individual places before these individual tables. For the tables marked with (E), (F), (G) (H), (I) and (J), the individual traveling time is preset for the conveying container 800 to travel between the second timer start gate 100b and individual places before these individual tables.

The timer start gate portions 100a, 100b may use an electric wave, a magnetic field, or a photoelectric discharge tube, in addition to the infrared radiation.

660200-ET637200

The conveying container 800 includes a dish-like casing 810 opening at the top and assembling in a lower portion thereof the microcomputer 94, a battery (not shown) of a source of electrical energy of the microcomputer 94, etc.. The casing 810 has at a lower side thereof an input portion 820
5 having press button switches 830 which are marked corresponding to the tables 2 marked with (A), (B), (C), (D), (E), (F), (G), (H), (I) and (J) so that the press button switch 830 having the mark corresponding to the orderer's table can be pressed to input the designated table's mark to the input portion.

10 The casing 810 is provided at a lower side thereof with a speaker 840 of the noticing means, so that when the order comes near the orderer's table, the arrival of the order is announced by means of the speaker 840.

With this constructed food and drink conveying system, the food e.g. sushi ordered is dished up on the plate 5 in the kitchen 3 and then the plate
15 5 is placed in the conveying container 800. After the press button switch 830 having the mark corresponding to the orderer's table is pressed to input the designated table mark to the input portion, the conveying container 800 is placed on the flat chain 73 of the conveying path 7 to convey it to the dinning area 1.

20 When the orderer's table is any one of the tables marked with (A), (B), (C) and (D), the conveying container 800 is placed on the conveying path 7 at a position upstream from the first timer start gate portion 100a. On the other hand, when the orderer's table is any one of the tables marked with (E), (F), (G) (H), (I) and (J), the conveying container 800 is placed on the
25 conveying path 7 at a position upstream from the second timer start gate

portion 100b.

In the conveying container 800 placed on the conveying path 7, the timer 93 starts at a point in time when the conveying container 800 passes the timer start gate portion 100a or 100b and runs out near the orderer's table, and then the speaker 840 is put in motion for announcement under control of the microcomputer 94. Thus, the orderer can surely aware of his/her order arriving at his/her table even in the middle of eating and drinking and chatting.

According to this embodiment, since the timer 93 starts at a point in time when the conveying container passes the timer start gate portion 100a or 100b, the order can surely be announced by means of the speaker 840 at a place near the orderer's table, irrespective of variations in, for example, location of the conveying container 800 placed on the conveying path 7 or timing of the push of the button switches 830. Thus, the order can be announced just at the right time to always let the orderer know his/her order with accuracy.

In this embodiment also, a conveying container having a similar structure to those capable of retracting therein the food and drink as shown in FIGS. 2 and 6 may be used as a substitute for the conveying container 800.

Additionally, the illustrated embodied forms of the operation control means for controlling the operation of the noticing means may be modified such that the respective tables and the counter 2a and 2b are provided with transmitters for the individual marked or numbered tables, while on the other hand, the conveying container 8, 80 or 800 is provided with a counting

means for receiving information transmitted from the transmitters to count the table numbers, so that when the counting means counts the immediately preceding number of the table numbers input to the input portion 82 or 820, the noticing means can be put in motion.

5 Also, the speaker 84 or 840 and the lamp 85 forming the noticing means which in illustration are arranged in the conveying container may be arranged on the table side.

EMBODIMENT 4

Further, FIGS. 10 to 13 show a further modified embodiment of the
10 present invention. As the basic construction of the food and drink conveying system 6 of this embodiment is identical to that of the embodiment 3, the difference in construction only will be described below.

In the embodiment shown in FIGS. 10 to 13, a shorting mechanism
15 700 for bridging parts of the conveying path 7 is arranged in some midpoint of the conveying path 7 in the second housing portion 4b.

The shorting mechanism 700 is basically composed of a short conveying path 701 and a pair of first and second guiding members 702 and 703.

The short conveying path 701 is arranged in some midpoint of the
20 second housing portion 4b, as schematically shown in FIG. 10, so that the conveyance of the food and drink to the tables marked with (B) and (C) arranged in the second housing portion 4b can be brought to rest. The short conveying path 701 is provided with a pair of rollers 704, a conveying belt 705 spreading between the rollers 704 in endless relation, and a motor (not
25 shown) as a drive for rotating one of the rollers 704.

5 A first guide member 702 is provided at an inlet side of the short conveying path 701, for letting the plate 5 conveyed by the conveying path 7 transfer to the short conveying path 701. A second guide member 703 is provided at an outlet side of the short conveying path 701, for letting the plate 5 conveyed by the short conveying path 701 transfer to the conveying path 7. The first and second guide members 702, 703 are swingably pivoted to pivot shafts 707, respectively, and the pivot shafts 707 are associated with the drive 708 of the motor at lower portions thereof so that the guide members 702, 703 can automatically be swung about the pivot shafts 707 in a substantially horizontal direction to intersect to the conveying path 7.

10 The shorting mechanism 700 is provided with a short drive detector 97 for detecting the switching to the short drive caused by the first guide member 702 being swung to such a position as to intersect to the conveying path 7.

15 The timer facility 95 in which individual traveling time for the conveying container 800 to travel to the respective tables is preset is constructed on a program of the microcomputer 94 forming the operation control means. To the input portion of the microcomputer 94 is connected a receiver 98 for receiving detected signals from the short drive detector 97 detecting the switching to the short drive caused by the first guide member 702 being swung to such a position as to intersect to the conveying path 7.

20 In the timer facility 95 is preset the individual traveling time required for the conveying container 800 to travel to the individual tables. For the tables marked with (A), (B), (C) and (D), the individual traveling time is

preset for the conveying container 800 to travel between the first timer start gate 100a and individual places before these individual tables. For the table (D) in particular, two possible traveling time is preset for the conveying container to reach the table without and with passing through the short conveying path 701 of the shorting mechanism 700.

For the tables marked with (E), (F), (G) (H), (I) and (J), the individual traveling time is preset for the conveying container 800 to travel between the second timer start gate 100b and individual places before these tables, as in the case of the embodiment above.

With this constructed food and drink conveying system, the food e.g. sushi ordered is dished up on the plate 5 in the kitchen 3 and then the plate 5 is placed in the conveying container 800. After the press button switch 830 having the mark corresponding to the orderer's table is pressed to input the designated table mark to the input portion, the conveying container 800 is placed on the flat chain 73 of the conveying path 7 to convey it to the dinning area 1.

By the way, the so-called short drive mode, in which the short conveying path 701 of the shorting mechanism 700 is driven to bridge parts of the conveying path 7 with the both guide members 702, 703, so as not to convey any food and drink to the tables marked with (B) and (C), is detected by the short drive detector 97. When the order is received from the table (D) in this short drive mode, the food e.g. sushi ordered is dished up on the plate 5 and then the plate 5 is placed in the conveying container 800. After the press button switch 830 having the mark corresponding to the orderer's table is pressed, the conveying container 800 is placed on the flat chain 73 of

the conveying path 7 to convey it to the dinning area 1.

Then, at a point in time when the conveying container 800 placed on the conveying path 7 passes the timer start gate portion 100a, the timer of the timer facility 95 starts, selecting the traveling time required for the conveying container to reach the table (D) with passing through the short conveying path 701 of the shorting mechanism 700. Accordingly, even when the short drive is in operation, the preset timer 93 runs out near the orderer's table (D) with accuracy and the speaker 840 is then put in motion for announcement under the control of the microcomputer 94.

In this embodiment also, a conveying container having a similar structure to those capable of retracting therein the food and drink as shown in FIGS. 2 and 6 may be used as a substitute for the conveying container 800.

Also, the speaker 84 or 840 and the lamp 85 forming the noticing means which in illustration are arranged in the conveying container may be arranged on the table side.

WHAT IS CLAIMED IS:

1. A food and drink conveying system comprising:
a conveying path for making a circulation of food and drink;
a plurality of tables arranged along the conveying path;
5 a conveying container which contains therein the food or the
drink and is placed on the conveying path; and
a noticing means for giving an orderer a notice of an arrival of
his/her order contained in the conveying container.

2. A food and drink conveying system according to Claim 1, wherein
10 the conveying container is provided with an input portion to which a
designated table's mark is input and operation control means for
controlling operation of the noticing means by an input by means of
the input portion.

3. A food and drink conveying system according to Claim 1, wherein
15 the conveying container has a retracting portion in which the food or
the drink is kept retracted until a notice by means of the noticing
means is started and from which the food or the drink is exposed to
be taken out when the notice by means of the noticing means is started.

4. A food and drink conveying system according to Claim 2, wherein
20 the conveying container has a retracting portion in which the food or
the drink is kept retracted until a notice by means of the noticing
means is started and from which the food or the drink is exposed to
be taken out when the notice by means of the noticing means is started.

5. A food and drink conveying system according to Claim 2, wherein the operation control means is provided with a timer facility in which traveling time for the conveying container to travel to the individual tables is preset and wherein the conveying path is provided with a timer start gate portion for letting the timer of the timer facility start so that at a point in time when the conveying container placed on the conveying path passes the timer start gate portion, the timer of the timer facility can be started.

6. A food and drink conveying system according to Claim 3, wherein the operation control means is provided with a timer facility in which traveling time for the conveying container to travel to the individual tables is preset and wherein the conveying path is provided with a timer start gate portion for letting the timer of the timer facility start so that at a point in time when the conveying container placed on the conveying path passes the timer start gate portion, the timer of the timer facility can be started.

7. A food and drink conveying system according to Claim 4, wherein the operation control means is provided with a timer facility in which traveling time for the conveying container to travel to the individual tables is preset and wherein the conveying path is provided with a timer start gate portion for letting the timer of the timer facility start so that at a point in time when the conveying container placed on the conveying path passes the timer start gate portion, the timer of the timer facility can be started.

ABSTRACT

The present invention relates to a food and drink conveying system including a conveying path for making a circulation of a plurality of containers each containing therein food and drink; and a plurality of tables arranged along the conveying path. The food and drink conveying system of the invention includes a conveying container which contains therein the container placing thereon a food or drink and is placed on the conveying path; and noticing means for letting an orderer know an arrival of his/her order contained in the conveying container at a place near the orderer's table, so that the order can surely be received by the customer, without any fear of the customer's order being taken away on the way to the order's table by another person by mistake

Fig. 1




Fig. 2




Fig. 3




Fig. 4




Fig. 6




Fig. 8




Fig. 7




Fig.10




Fig.11




Fig. 12





Fig.13



APPLICATION FOR UNITED STATES LETTERS PATENT**Declaration and Power of Attorney**

As a below named inventor, I declare that:

My residence, post office address and citizenship are as stated below next to my name; I believe that I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled:

FOOD AND DRINK CONVEYING SYSTEM

the specification of which is attached hereto.

I have reviewed and understand the contents of said specification, including the claims.

I acknowledge the duty to disclose information which is material to patentability as defined in 37 CFR §1.56.

I claim priority benefits under 35 USC §119 of: (i) any foreign application(s) for patent or inventor's certificate listed below; or (ii) any United States provisional application(s) listed below; and have also identified below any foreign application(s) for patent or inventor's certificate, or PCT international application having a filing date before that of the application(s) on which priority is claimed.


COUNTRY	APPLICATION NUMBER	DATE (day, month, year)	PRIORITY CLAIMED
Japan	10-31538	13/02/1998	yes <input checked="" type="checkbox"/> no <input type="checkbox"/>
Japan	10-350201	09/12/1998	yes <input checked="" type="checkbox"/> no <input type="checkbox"/>

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

I appoint the following attorneys to prosecute this application and to transact all business in the U.S. Patent & Trademark Office connected therewith: Stephen H. Frishauf, Reg. No. 16,233; Leonard Holtz, Reg. No. 22,974; Herbert Goodman, Reg. No. 17,081; Thomas Langer, Reg. No. 27,264; Marshall J. Chick, Reg. No. 26,853; Walter J. Baum, Reg. No. 20,641; Richard S. Barth, Reg. No. 28,180; Douglas Holtz, Reg. No. 33,902; and Robert P. Michal, Reg. No. 35,614.

CORRESPONDENCE AND CALLS TO: FRISHAUF, HOLTZ, GOODMAN, LANGER & CHICK, P.C.
767 Third Avenue - 25th Floor Tel.: (212) 319-4900
New York, New York 10017 Fax.: (212) 319-5101

INVENTOR: SIGNATURE**DATE****RESIDENCE AND POST OFFICE ADDRESS**

Sign: 	Date: Feb. 5, 1999	Residence (City & Country): Sakai-shi, Osaka JAPAN
Type: Kunihiro TANAKA	Citizen of: Japan	Post Office Address: c/o Kura Corporation Ltd., 1035-2, Fukasaka, Sakai-shi, Osaka JAPAN
Sign:	Date:	Residence (City and Country):
Type:	Citizen of:	Post Office Address:
Sign:	Date:	Residence (City and Country):
Type:	Citizen of:	Post Office Address: